

VARIABLES, EXPRESSIONS AND FUNCTIONS

Today

- Answer more questions on:
 - Midterm
 - Homework for Unit B
- Talk about variable, expressions and functions in the context of Netlogo and Javascript.
- Remind you to do the readings for Units D, E and F.

Any questions?

Netlogo as Computer Science

- Here's a small piece of Netlogo:

```
to catch-sheep
  let prey one-of (sheep-here
                    with [not grabbed?])
  if prey != nobody
  [ set grabbed?-of prey true
    ask prey [ die ]
    set energy energy + wolf-gain-from-food
  ]
end
```
- What's going on here?

What's going on?

- This is something that we tell a wolf to do in the wolf/sheep model.
- We tell it to make “prey” one of the sheep on the patch that the wolf is on, one which is not “grabbed?”.
- If there is such a sheep, we tell the wolf:
 - mark it as “grabbed?”
 - make the sheep die
 - get more energy from eating the sheep.
- What does the computer have to do to make this work?

Variables

- One thing we need is for each sheep to know whether it has been “grabbed” or not.
- Why is this important?
- So that the sheep can tell, we give it a *local variable*:

```
sheep-own [ grabbed? ]
```

it is “local” because each sheep has its own — it is local to the individual sheep.

- Since “grabbed?” belongs to the sheep, when the wolf changes it, it has to use:

```
set grabbed?-of prey true
```

rather than:

```
set grabbed? true
```

Variables (more)

- We say that the *scope* of the variable grabbed? is the sheep.
- Because the variable is local, not every agent can access it.
- Indeed, only a single sheep can access each grabbed?.
- In contrast, this is a *global variable*:

```
globals [ ticks ]
```

- Since ticks is global, any agent can find out the value of ticks.

Variables (even more)

- Here are some more local variables:

```
turtles-own [ energy ]
```

```
patches-own [ countdown ]
```

- Other variables that you have come across are pcolor, xcor, ycor, pxcor, pycor.
- In general, variables give us a way to *store values*.

Variables (last)

- Our example from wolf/sheep shows another kind of local variable.

```
let prey one-of (sheep-here  
                with [not grabbed?])
```

- Here prey is a variable that is local to catch-sheep, rather than to any turtle.
- The scope of prey is catch-sheep.
- Trying to access prey from outside catch-sheep will give an error.

Expressions

- A variable gives us a way to store a value.
- An *expression* gives us a way to compute a value.
- The most common way we have used expressions is when we have used set.

```
set energy energy + wolf-gain-from-food
```

Expressions (more)

- Wolf/sheep also gives us these examples

```
set pcolor green
```

```
set color black
```

```
rt random-float 50 - random-float 50
```

```
set energy random (2 * wolf-gain-from-food)
```

- What is going on in these?

Expressions (even more)

- `set` is an example of *assignment*. It changes the value of a variable.
- ```
set energy energy + wolf-gain-from-food
```

changes the value of the variable `energy` to be the old value of `energy` plus the value of `wolf-gain-from-food`.
- ```
set color black
```

changes the value of the variable `color` to be black

Expressions (last)

- ```
rt random-float 50 - random-float 50
```

  

```
set energy random (2 * wolf-gain-from-food)
```

make use of *functions*, `random` and `random-float`

### Functions (first time)

- Functions are bits of program that generate *values*.
- Since they generate values, it is natural that we use them along with assignment.
- We use functions as a way to get *abstraction*.
- You can think of abstraction as “hiding the detail”.
- Rather than writing out the Netlogo code for generating a random number every time that we want one, we just call `random`.
- `random` is provided by the folk who wrote Netlogo, but you can also write your own functions.

### Procedures

- In fact we don't write many of our own functions in Netlogo.
- We do write *procedures*. Procedures are bits of code that *do something*:
- `catch-sheep` is a nice example.  

```
to catch-sheep
 let prey one-of (sheep-here
 with [not grabbed?])
 if prey != nobody
 [set grabbed?-of prey true
 ask prey [die]
 set energy energy + wolf-gain-from-food
]
end
```

### Procedures (more)

- A procedure starts with:  
`to name-of-procedure`  
  
and ends with  
`end`
- In between, the procedure contains a list of instructions.
- These instructions are the steps in the *algorithm* that the procedure uses.

### Procedures (even more)

- You then *call* a procedure to make it execute.

```
to go
:
 ask wolves [
 move
 set energy energy - 1
 catch-sheep
 reproduce-wolves
 death]
:
end
```

- So one procedure is called by a second procedure which may be called by a third procedure, and so on ....

### Procedures (last)

- Procedures can take inputs:  
  
`to draw-polygon [num-sides len]`  
`pd`  
`repeat num-sides`  
`[ fd len`  
`rt (360 / num-sides) ]`  
`end`
- To call this procedure, you have to give it a number (an integer) that sets the number of sides, and another number (integer) that sets the length of the sides.  
  
`ask turtles [ draw-polygon 8 who ]`

### Functions (again)

- In Netlogo, functions are called *reporters*.
- They report values.
- They are defined and called much like procedures:

```
to-report absolute-value [number]
 ifelse number >= 0
 [report number]
 [report 0 - number]
end
```

## Summary

- This lecture talked about some of the computer science ideas behind Netlogo.
  - Variables
  - Expressions
  - Functions