HEURISTIC SEARCH II

Recap

The last lecture introduced

- More advanced problem solving techniques:
 - Depth limited search
 - Iterative deepening
 - Bidirectional search
- These improved on basic techniques like breadth-first and depth-first search.
- However, they still aren't powerful enough to give solutions for realistic problems.
- Are there more improvements we can make?

Overview

Aims of this lecture:

- To show how applying some knowledge of the problem can help.
- Introduce *heuristics* rules of thumb.
- Introduce *heuristic search*: guided by rules of thumb which help to decide which node to expand:
 - uniform-cost search;
 - greedy search;
 - $-A^*$ search.

Heuristic (Informed) Search

- Whatever search technique we use, *exponential time complexity*.
- Tweaks to the algorithm will not reduce this to polynomial.
- We need problem specific knowledge to guide the search.
- Simplest form of problem specific knowledge is *heuristic*.
- Usual implementation in search is via an *evaluation function* which indicates desirability of expanding node.

Uniform Cost Search

• Recall we have a *path cost function*,

 $g: Nodes \rightarrow R$

which gives cost to each path.

- Why not expand the *cheapest* path first?
- Intuition: cheapest is likely to be best!

```
• General algorithm for uniform search:
 agenda = initial state;
while agenda not empty do
   take node from agenda such that
     g(node) = min \{ g(n) \mid n in agenda \}
   new nodes = apply operations to node;
   if goal state in new nodes then {
     return solution;
   else add new nodes to agenda
```

- Uniform cost search guaranteed to find cheapest solution *assuming path costs grow monotonically*.
- In other words, adding another step to the solution makes it more costly.
- If path costs *don't* grow monotonically, then exhaustive search is required.

• Once again we can illustrate this on the 8-puzzle:



1	2	3	
8		4	
7	6	5	

• For this set up, the search of the space:



- Will happen in the following way.
- States would be expanded in the order:

```
    1. 1
    2. 2, 3, 4
    3. 5, 6, 7, 8, 9
    4. 10, 11, 12, 13, 14, 15, 16, 17, 18, 19
    5. ...
```

• Note that this is just like breadth first search (because the path costs are just the same).

- Instead, assume up/down moves cost 2 and left/right moves cost 1.
- States would be expanded in the order:

1. 1
 2. 2, 3, 4
 3. 5
 4. 9
 5. 6, 7, 8
 6. ...

Greedy Search

- Most heuristics *estimate cost of cheapest path from node to solution*.
- We have a *heuristic function*,

 $h: Nodes \rightarrow R$

which estimates the distance from the node to the goal.

- Example: In route finding, heuristic might be straight line distance from node to destination.
- Heuristic is said to be *admissible* if it *never overestimates* cheapest solution.

Admissible = optimistic.

• Greedy search involves *expanding node with cheapest expected cost to solution*.

```
• General algorithm for greedy search:
 agenda = initial state;
while agenda not empty do
   take node from agenda such that
     h(node) = min \{ h(n) | n in agenda \}
   new nodes = apply operations to node;
   if goal state in new nodes then {
     return solution;
   else add new nodes to agenda
```

- Greedy search finds solutions quickly.
- Doesn't always find best.
- Susceptible to false starts.
 - Chases good looking options that turn out to be bad.
- Only looks at *current* node. Ignores past!
- Also *myopic* (shortsighted).

- For the 8-puzzle one good heuristic is:
 - count tiles out of place.
- Another is:
 - Manhattan blocks' distance
- The latter works for other problems as well:
 - Robot navigation.



A* Search

- A* is very efficient search strategy.
- Basic idea is to *combine*

uniform cost search *and* greedy search.

- We look at the *cost so far* and the *estimated cost to goal*.
- Gives heuristic *f*:

f(n) = g(n) + h(n)

where

- -g(n) is path cost of *n*;
- h(n) is expected cost of cheapest solution from n.
- Aims to mimimise *overall cost*.

```
• General algorithm for A* search:
 agenda = initial state;
while agenda not empty do
   take node from agenda such that
     f(node) = min \{ f(n) | n in agenda \}
     where f(n) = g(n) + h(n)
   new nodes = apply operations to node;
   if goal state in new nodes then {
     return solution;
   else add new nodes to agenda
```

- Considering the 8-puzzle (for the last time :-):
- We combine:
 - Path cost function:
 - * number of moves.
 - Heuristic function:
 - * tiles out of places.
- This gives the following search.



cis32-fall-2005-parsons-lect08

20

The optimality of A*

- A* is optimal in precise sense—it is guaranteed to find a minimum cost path to the goal.
- There are a set of conditions under which A* will find such a path:
 - 1. Each node in the graph has a finite number of children.
 - 2. All arcs have a cost greater than some positive ϵ .
 - 3. For all nodes in the graph h(n) always underestimates the true distance to the goal.
- The key here is the third bullet the notion of *admissibility*.
- We will express this by saying a heuristic $h(\cdot)$ is admissible if

 $h(n) \leq h_T(n)$

More informed search

IF two versions of A*, A^{*}₁ and A^{*}₂ use different functions h₁ and h₂,
AND

$$h_1(n) < h_2(n)$$

for all non-goal nodes,

- THEN we say that A_2^* is *more informed* than A_1^* .
- The better informed A* is, the less nodes it has to expand to find the minimum cost path.

- As an example of "more informed" consider the 8-puzzle:
 - tiles out of place; and
 - Manhattan blocks distance.
- We need h(n) to underestimate $h_T(n)$ to ensure admissibility.
- But, the closer the estimate, the easier it is to reject nodes which are not on the optimal path.
- This means less nodes need to be searched.

Iterative deepening A*

- When we do heuristic search, we search some portion of the full search space.
- "Focussed breadth first search".
- So we can still hit intractability.
- Adapting iterative deepening can help us.
- Instead of a depth limit, we impose a cost limit, and do a depth first search until it is exceeded.
- Then we backtrack, and extend the limit if we don't find the goal.

- The initial cost cut off is set to $f(n_0)$.
- This is just the estimated cost of finding a solution $h(n_0)$.
- This will never overestimate the cost, so is a good start point.
- If this cost-limit does not provide a solution, what is the next cost limit.
- Well, if the heuristic is a good one, the cost of the cheapest path to the goal will be the lowest *f*(*n*) of an unexpanded node.
- So we set the new cost bound to this.
- This, then is iterative deepening A* (IDA*).

Summary

- This lecture has looked at some techniques for refining the search space:
 - uniform cost search;
 - greedy search; and
 - A* search.
- When these work they explore just the relevant part of the search space.
- There are also techniques that go further than those we have studied.

- These techniques include:
 - Focussed Dynamic A* (called D*)
 - D* Lite
 - Delayed D*
 - Life-long planning A* (called LPA*)
 - **–** PAO*
- There are three directions we will take from here:
 - Adversarial search
 - Learning the state space.
 - Adding in more knowledge about the domain.