

CS1007 lecture #8 notes

thu 14 feb 2002 ♡

- news
- `java.lang` package
- looping
- increment/decrement operators
- reading: ch 2.5-2.7, 3.5-3.8

news.

- homework #2 is due today
- midterm #1 next thursday (21 feb)

classes.

- *classes* are the block around which Java is organized
- classes are composed of
 - data elements:
 - * *variables* — i.e., their values can change during the execution of a program
 - * *constants* — i.e., their values **CANNOT** change during the execution of a program
 - like variables, they have a type, a name and a value
 - *methods*
 - * modules that perform actions on the data elements
 - like variables, they have a type, a name and a value
 - unlike variables, the type can be *void*, which means that they don't really have a value
 - * *constructors* — special types of methods used to set up an object before it is used for the first time
- groups of related classes are organized into *packages*

the `java.lang` package.

- the superclass for all Java classes, at the top of the hierarchy
 - `java.lang.Object`
- wrappers around primitive data types; classes that define numeric limits and contain conversion methods
 - `java.lang.Boolean`
 - `java.lang.Character`
 - `java.lang.Byte`, `java.lang.Short`, `java.lang.Integer`, `java.lang.Long`, `java.lang.Float`, `java.lang.Double`
- string handling functions
 - `java.lang.String`
- math functions
 - `java.lang.Math`

java.lang.Integer class.

- a *constructor*:
public Integer(int value);
- some *constants*:
public static final int MIN_VALUE
public static final int MAX_VALUE
- some *methods*:
public int intValue();
public static String toString(int i);
public static Integer valueOf(String s);

java.lang.String class.

- some *constructors*:
public String();
public String(String value);
- some *methods*:
public static String valueOf(int i);
public int charAt(int index);
public int compareTo(String anotherString);
public int length();

java.lang.Math class.

- some *constants*:
public static final double E
public static final double PI
- some *methods*:
public static int abs(int a);

public static native double sin(double a);
public static native double cos(double a);
public static native double tan(double a);

public static native double pow(double a, double b);
public static native double sqrt(double a);

public static double random();

looping.

- if you want to do something many times
- two types of loops:
 - counter controlled
 - condition controlled
- three loop statements:
 - `for`
 - `while`
 - `do`

for loop.

```
public class ex8 {  
    public static void main ( String[] args ) {  
        Integer tmp;  
        int    n, i;  
        tmp = Integer.valueOf( args[0] ); // String -> Integer  
        n = tmp.intValue();              // Integer -> int  
        System.out.println( "counting up to " + n + "... " );  
        for ( i=0; i<n; i++ ) {  
            System.out.print( i+ " " );  
        } // end for  
        System.out.println();  
    } // end of main  
} // end of class ex8
```

increment and decrement operators.

- increment: ++
i++;
is the same as:
i = i + 1;
- decrement: --
i--;
is the same as:
i = i - 1;