Quick and Dirty EMACS

Note that any ordinary character goes into the buffer (no insert is needed). For a more detailed emacs manual, check out the GNU emacs manual on-line at:

http://www.gnu.org/software/emacs/manual/

Some necessary abbreviations:

C- a control character, hit the control key (CTRL) and the character key simultaneously M- a two-character command sequence where the first character is the escape key (ESC) (CR) the carriage return key

Cursor operations:

C-B	move left (backwards)
C-F	move right (forwards)
C-P	move up a line (previous)
C-N	move down a line(next)
DELETE	delete character to the left
C-D	delete character to the right
C-T	transpose two characters to the left (th \rightarrow ht)

Word operations:

M-B	move left (backwards)
M-F	move right (forwards)
M-DELETE	kill word to the left (C-Y yanks it back)
M-D	kill word to the right (C-Y yanks it back)
M-T	transpose two words around cursor (if only \rightarrow only if)
M-C	capitalize word (first letter only)
M-U	uppercase entire word
M-L	lowercase entire word

Line operations:

C-A	move cursor to the beginning of the line
C-E	move cursor to the end of the line
C-K	kill from cursor to end of line (C-Y yanks it back)
M-0 C-K	kill from beginning of line to cursor (C-Y yanks it back)

Sentence operations:

```
    M-A move cursor to beginning of sentence
    M-E move cursor to end of sentence
    M-K kill from cursor to end of sentence (C-Y yanks it back)
```

Paragraph operations:

```
M-[ move cursor to beginning of paragraphM-] move cursor to end of paragraph
```

Screen operations:

C-V show next screen M-V show previous screen

C-L redisplay screen so that line with cursor on it is in the middle of the screen

M-0 C-L move line with cursor on it to top of screen

Buffer operations:

C-X C-F get a file into a buffer for editing

M-< move cursor to top of the current buffer
M-> move cursor to bottom of the current buffer

Search and Replace:

C-G terminates all searches (sometimes you have to hit it twice)

C-S string search for "string"

C-R string reverse search for "string"

M-X % string1(CR) string2(CR) the \$ is the result of hitting the M- key,

search for "string1" and query: replace it with "string2"?

if yes, hit the space bar or Y key

if no, hit the N key

halt the procedure with C-G

Leaving:

C-X C-S write the current buffer into a new version of the current file name

C-X C-W write the current buffer into a file with a different name

C-X C-Z EXIT EMACS

Abort, Undo and Help:

C-G abort anything at any time (it beeps, sometimes you need to hit it twice)

C-_ undo last keystroke

M-X Undo M- restore the buffer before the last kill, unkill, fill, sort, etc.

C-Y yank back the last thing killed

C-H help